



Design Pro LED Controller - 300W

Item Number	15DC300 - 300W
Zones	Up to 6 independently controlled zones
Weight	11 lbs.

GENERAL SPECIFICATIONS – FOR ALL 3 CONTROLLERS (cont.)

Potting	Fully encapsulated potted electronics	
Timer	Integrated astronomical clock programmable by geolocation	
Efficiency on Primary Power Side	Minimum 85% (power-in, power-out)	
UL Listing & FCC	ANSI/UL 1838 CSA 250.7	FCC Part 15B
Location Use	Wet location rated, outdoor use. Indoor acceptable by local code.	
Transformer Type	Electronic DC (low ripple and acceptable for use LED Landscape fixtures)	
System Information	Calculates live watts and amperage within zone summary	
Overload Protection	Yes	
Menu Diagnostics	Yes, to aid in troubleshooting common problems	
Conduit Adaptor	1" trade-size PVC slip fit conduit adaptor for a clean and professional installation. Can also accept 1.25" trade size PVC conduit.	
Wireless Type & Range	Z-Wave®. See Z-wave.com for additional options. 300' line of sight range. Vera Wireless Gateway compatible.	
Network	Multiple controllers can be wirelessly synced together to create a network (maximum 4 controllers in 1 network). Multiple networks can be set-up in installations with more than 4 controllers.	

Dimensions	15DC100	15DC200	15DC300
	Height = 13.73" Depth = 4.46" Width = 8.62" 	Height = 13.71" Depth = 4.46" Width = 13.51" 	Height = 13.71" Depth = 4.46" Width = 13.51" 



Z-Wave is a registered trademark of Sigma Design and its subsidiaries in the United States and other countries. For recommended third party accessories, please contact Kichler for a tested list.