

Transformers

Professional Series
Contractor Series



“ The stainless steel transformer not only looks great and installs in under 10min but also has a great warranty. Highly recommend by myself and many others in my profession ”

- Polermnky | Edwardsville, IL | 15PR300SS



	Professional Series PR – 100W-1200W	Professional Series PR – 75W
Finish	#304 Stainless Steel	#304 Stainless Steel
Item Number with Wattage	15PR100SS - 100W 15PR600SS - 600W 15PR200SS - 200W 15PR900SS - 900W 15PR300SS - 300W 15PR1200SS - 1200W	15PR75SS - 75W
Input Voltage	120V	120V
Output Multi-Taps	12/13/14/15 Volts. 2 separate sets of multi-tap output with angled terminal blocks for easy wire input.	15 Volts, with angled terminal blocks for easy wire input
Core and Coil	High-efficiency E.I. core and coil configuration (100W-600W). High-efficiency toroid core and coil (900W-1200W).	High-efficiency toroid core and coil configuration
Door Style	Easy magnetic flip-and-stay-open door	Easy magnetic flip-and-stay-open door
Easy-Connect Terminal Lug Capacity	Up to 8, #10-gauge wires or up to 10, #12-gauge wires per tap	Up to 8, #10-gauge wires or up to 10, #12-gauge wires per tap
Secondary Side Protection	Magnetic breaker	Magnetic breaker
Timer/Photocell	Compatible with plug-in timer and plug-in photocells	Compatible with plug-in timer and plug-in photocells
Cord	6' of usable SJTW cord	6' of usable #18-3 SJTW cord
Conduit Knockouts	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet
Notes	Includes mounting hardware. Dedicated wire loop for testing primary voltage.	Includes mounting hardware
Accessories	15556WH Digital Timer 15557BK Mechanical Timer 15565BK Standard Photocell 15534BK 10' Remote Photocell 15511BK Synchronizer	15556WH Digital Timer 15557BK Mechanical Timer 15565BK Standard Photocell 15534BK 10' Remote Photocell 15511BK Synchronizer
Dimensions	19" L x 5.5" W x 5.75" D - 100W-300W 19" L x 6.75" W x 5.75" D - 600W 21" L x 6.75" W x 6" D - 900W 17.5" L x 8" W x 7" D - 1200W	16.5" L x 5.5" W x 5.75" D