

Transformers

Contractor Series



	Contractor Series CS – 150W	Contractor Series CS – 300W
Finish	#304 Stainless Steel	#304 Stainless Steel
Item Number with Wattage	15CS150SS - 150W	15CS300SS - 300W
Input Voltage	120V	120V
Output Multi-Taps	12/13/14/15 Volts	12/13/14/15 Volts
Core and Coil	High-efficiency fully encapsulated toroidal	High-efficiency fully encapsulated toroidal
Door Style	Fully removable hinge-style door with buckle latch	Fully removable hinge-style door with buckle latch
Easy-Connect Terminal Lug Capacity	Up to 10, #12-gauge wires per tap	Up to 10, #12-gauge wires per tap
Secondary Side Protection	Magnetic breaker	Magnetic breaker
Timer/Photocell	Compatible with plug-in timer and photocells	Compatible with plug-in timer and photocells
Cord	6' of usable #18-3 SJTW cord	6' of usable #18-3 SJTW cord
Conduit Knockouts	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet
Notes	Includes mounting hardware. Dedicated wire loop for testing primary voltage. Department of Energy certified. Safety listings: cUL 1838, CSA 22.2.	Includes mounting hardware. Dedicated wire loop for testing primary voltage. Department of Energy certified. Safety listings: cUL 1838, CSA 22.2.
Accessories	15556WH Digital Timer 15557BK Mechanical Timer 15565BK Standard Photocell 15534BK 10' Remote Photocell 15511BK Synchronizer	15556WH Digital Timer 15557BK Mechanical Timer 15565BK Standard Photocell 15534BK 10' Remote Photocell 15511BK Synchronizer
Dimensions	13" L x 5.55" W x 5.51" D	13" L x 5.55" W x 5.51" D