



	Contractor Series CS – 600W	Contractor Series CS – 900W
Finish	<b>#304 Stainless Steel</b>	<b>#304 Stainless Steel</b>
Item Number with Wattage	<b>15CS600SS - 600W</b>	<b>15CS900SS - 900W</b>
Input Voltage	120V	120V
Output Multi-Taps	12/13/14/15 Volts	12/13/14/15 Volts
Core and Coil	High-efficiency fully encapsulated toroidal	High-efficiency fully encapsulated toroidal
Door Style	Fully removable hinge-style door with buckle latch	Fully removable hinge-style door with buckle latch
Easy-Connect Terminal Lug Capacity	Up to 10, #12-gauge wires per tap	Up to 10, #12-gauge wires per tap
Secondary Side Protection	Magnetic breaker	Magnetic breaker
Timer/Photocell	Compatible with plug-in timer and photocells	Compatible with plug-in timer and photocells
Cord	6' of usable #18-3 SJTW cord	6' of usable #18-3 SJTW cord
Conduit Knockouts	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet	8 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet
Notes	Includes mounting hardware. Dedicated wire loop for testing primary voltage. Department of Energy certified. Safety listings: cUL 1838, CSA 22.2.	Includes mounting hardware. Dedicated wire loop for testing primary voltage. Department of Energy certified. Safety listings: cUL 1838, CSA 22.2.
Accessories	<b>15556WH</b> Digital Timer <b>15557BK</b> Mechanical Timer <b>15565BK</b> Standard Photocell <b>15534BK</b> 10' Remote Photocell <b>15511BK</b> Synchronizer	<b>15556WH</b> Digital Timer <b>15557BK</b> Mechanical Timer <b>15565BK</b> Standard Photocell <b>15534BK</b> 10' Remote Photocell <b>15511BK</b> Synchronizer
Dimensions	<b>14.3" L x 6.65" W x 6.1" D</b>	<b>15.6" L x 7.8" W x 7.16" D</b>