



	<b>Plus Series PL – 75W</b>	<b>Manual Series M – 100W-600W</b>	
Finish	<b>AZT</b>		<b>AZT</b>
Item Number with Wattage	<b>15PL75AZT</b> - 75W	<b>15M100AZT</b> - 100W <b>15M200AZT</b> - 200W	<b>15M300AZT</b> - 300W <b>15M600AZT</b> - 600W
Input Voltage	120V	120V	
Output Multi-Taps	15 Volts	12 Volts	12/13/15 Volts
Core and Coil	High-efficiency fully encapsulated toroidal	High-efficiency E.I. core and coil configuration	
Door Style	Easy magnetic flip-and-stay-open door		
Easy-Connect Terminal Lug Capacity	Up to 8, #10-gauge wires or up to 10, #12-gauge wires per tap		
Secondary Side Protection	Magnetic breaker	Thermal reset breaker	Magnetic breaker
Timer/Photocell	Compatible with plug-in timer and plug-in photocells		
Cord	6' of usable #18-3 SJTW cord	6' of usable #18-3 SJTW cord (300W) 6' of usable #16-3 SJTW cord (600W only)	6' of usable #18-3 SJTW cord (100W-200W)
Conduit Knockouts	4 pre-punched field knockouts sized for .5" or .75" conduit (trade sizes) and one large center 1.75" inlet		
Notes	Includes mounting hardware		
Accessories	<b>15556WH</b> Digital Timer <b>15557BK</b> Mechanical Timer <b>15565BK</b> Standard Photocell <b>15534BK</b> 10' Remote Photocell <b>15511BK</b> Synchronizer		
Dimensions	16.5" L x 5.5" W x 5.75" D	8" L x 3.25" W x 3" D - 100W 13.25" L x 3.5" W x 4" D - 200W	13.5" L x 4.5" W x 4" D - 300W 14.25" L x 5.5" W x 5" D - 600W