

# Retrofit Accent



	Long Cowl Mini Accent	Architectural - Grade Adjustable		
Finishes	<b>AZT</b>	<b>AZT</b>		
Item Number and Finish	<b>15484 AZT</b>	<b>15397 AZT</b>		
Housing	Cast Aluminum with heat-resistant, fully sealed flat glass lens	Machined Aluminum with heat-resistant, fully sealed glass and angled for easy water run-off. Cowl is fully adjustable.		
Lamp Base	12V Bi-Pin, high-temperature porcelain socket			
Lamp Options-Power Usage at 12V AC input	<b>Incandescent:</b> 50W(VA) MR16 20W(VA) Max. Canada 35W(VA) MR11	<b>LED:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen	<b>Incandescent:</b> 50W(VA) MR16 35W(VA) Max. Canada 35W(VA) MR11	<b>LED:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen
Wiring	35" of usable #18-2, SPT-1W leads. Cable connectors supplied.	51" of usable #18-2, SPT-1W leads. Cable connectors supplied.		
Notes	Includes 8" slotted in-ground stake	Includes 8" slotted in-ground stake. Use with the 6" (15645), 12" (15656), 18" (15657) or 24" (15658) mounting stems for dramatic results.		
Accessories	<b>Mounting:</b> <b>15601</b> Surface Mounting Flange <b>15607</b> Surface Mounting Bracket <b>15609</b> Junction Box Mounting Bracket <b>15647</b> 90° Elbow <b>15649</b> Stem Coupler <b>15645, 15656, 15657, 15658, 15570</b> Stems	<b>Lens:</b> <b>15675 LIN</b> Linear Lens <b>15676 FRO</b> Frosted Lens <b>15679 BK</b> Hexcell Louver Shield <b>15683 BK</b> Louver <b>15686 BL</b> Blue Lens <b>15693 BL</b> Blue Lens		
Dimensions	<p>Illustrated with <b>15657</b> 18" mounting stem and <b>15649</b> stem coupler (both sold separately).</p>	<p>Illustrated with <b>15657</b> 18" mounting stem (sold separately).</p>		