

# Retrofit Accent



“Very pretty light. Brushed bronze look. Comes with heavy duty stake for ground. Glass is thick to protect light bulb. Adjustable on top so you can adjust where and how you want to shed the light.”

- Blarsen | Kalispell, MT | 15485CBR



	Accent		Composite
Finishes	<b>BKT (shown), AZT</b>		<b>BK</b>
Item Number and Finish	<b>15374 AZT</b> <b>15374 AZT20L</b> <b>15374 AZT20L24</b>	<b>15374 BKT</b> <b>15374 BKT20L</b> <b>15374 BKT20L24</b>	<b>15382 BK</b>
Housing	Cast Aluminum. with heat-resistant, fully sealed flat glass lens.		Components of durable high-heat thermoplastic composite resin. Heat-resistant flat glass lens is fully sealed.
Lamp Base	12V Bi-Pin, high-temperature porcelain socket		12V Bi-Pin, high-temperature porcelain socket
Lamp Options-Power Usage at 12V AC input	<b>Incandescent:</b> 50W(VA) MR16 20W(VA) Max. Canada	<b>LED:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen	<b>Incandescent:</b> 35W(VA) MR16  <b>LED:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen
Wiring	31" of usable #18-2, SPT-1W leads. Cable connectors supplied.		30" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Includes 8" slotted in-ground stake		Includes 8" slotted in-ground stake
Accessories	<b>Mounting:</b> 15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15609 Junction Box Mounting Bracket		15647 90° Elbow 15649 Stem Coupler 15645, 15656, 15657, 15658, 15570 Stems
	<b>Lens:</b> 15642 LIN Linear Lens 15643 FRO Frosted Lens 15644 BK Hexcell Louver Shield 15641 BL Blue Lens		<b>Lens:</b> 15674 LIN Linear Lens 15672 FRO Frosted Lens 15673 BL Blue Lens
Dimensions			