



| | MR16 Accent Fixed Socket Adjustable Cowl | MR16 Accent Fixed Socket |
|--|---|--|
| Finishes | CBR | CBR |
| Item Number and Finish | 15485 CBR | 15517 CBR |
| Housing | Cast Brass (CBR) | Cast Brass (CBR) |
| Lamp Base | 12V Bi-Pin, high-temperature porcelain socket | |
| Lamp Options-Power Usage at 12V AC input | LED only: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen | LED only: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen |
| Wiring | 30" of usable #18-2, SPT-1W leads. Cable connectors not included. | |
| Notes | Flat Glass; includes 8" slotted in-ground stake. Telescoping cowl allows for in-field beam adjustment. Brass will naturally patina over time. | Convex Glass; includes 8" slotted in-ground stake. Brass will naturally patina over time. |
| Accessories | Mounting: 15609 Junction Box Mounting Bracket 15489CBR Gutter Mount 15514CBR 90° Elbow 15515CBR Two Fixture Mount 15516CBR Surface Mount 15645, 15656, 15657, 15658, 15570, 15509, 15510, 15511, 15512, 15513 Stems Lens: 15675 LIN Linear Lens 15676 FRO Frosted Lens 15679 BK Hexcell Louver Shield 15686 BL Blue Lens | Mounting: 15609 Junction Box Mounting Bracket 15489CBR Gutter Mount 15514CBR 90° Elbow 15515CBR Two Fixture Mount 15516CBR Surface Mount 15645, 15656, 15657, 15658, 15570, 15509, 15510, 15511, 15512, 15513 Stems |
| Dimensions | | |