

Retrofit Accent



	Solid Brass Accent		MR16	
Finishes	CBR		BBR (shown), AZT, BKT	
Item Number and Finish	15475 CBR		15381 AZT 15381 AZT6	15381 BBR 15381 BKT
Housing	Cast Brass		Cast Aluminum or Cast Brass (BBR) with heat resistant, fully sealed, clear, flat glass lens	
Lamp Base	12V Bi-Pin, high-temperature porcelain socket		12V Bi-Pin, high-temperature porcelain socket	
Lamp Options-Power Usage at 12V AC input	Incandescent: 35W(VA) MR16	LED: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen	Incandescent: 75W(VA) MR16	LED: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen
Wiring	30" of usable #18-2, SPT-1W leads. Cable connectors supplied.		35" of usable #18-2, SPT-1W leads. Cable connectors supplied.	
Notes	Includes 8" slotted in-ground stake and cowl with convex lens. Not recommended for down light applications. Brass will naturally patina over time.		Includes 8" slotted in-ground stake. Brass will naturally patina over time.	
Accessories	Mounting: 15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15609 Junction Box Mounting Bracket		15647 90° Elbow 15649 Stem Coupler 15645, 15656, 15657, 15658, 15570 Stems LK87CBR Lock Nut	
	Lens: 15675 LIN Linear Lens 15676 FRO Frosted Lens 15679 BK Hexcell Louver Shield 15686 BL Blue Lens		Lens: 15692 LIN Linear Lens 15691 FRO Frosted Lens 15680 BK Hexcell Louver Shield 15687 BL Blue Lens	
Dimensions				

