



	Bi-Pin	PAR36 Uplight
Finishes	<b>AZT</b>	<b>CBR</b>
Item Number and Finish	<b>15383 AZT</b>	<b>15487 CBR</b>
Housing	Cast Aluminum with heat-resistant, fully sealed, clear, flat glass lens	Cast Brass
Lamp Base	12V Bi-Pin, high-temperature porcelain socket	12V PAR36 socket terminal
Lamp Options-Power Usage at 12V AC input	<p><b>Incandescent:</b> 75W(VA) MR16</p> <p><b>LED:</b> 1.2W T3/G4 Bi-Pin (18200, 18201) Compares up to 10W Halogen 2W T3/G4 Bi-Pin (18206, 18207) Compares up to 20W Halogen</p>	<p><b>LED only:</b> 4W PAR36 (18166-18173) Compares up to 20W Halogen 6W PAR36 (18174-18181) Compares up to 35W Halogen 10W PAR36 (18182-18189) Compares up to 50W Halogen 11W PAR36 (18021-18028) Compares up to 50W Halogen 14W PAR36 (18190-18197) Compares up to 75W Halogen</p>
Wiring	38" of usable #18-2, SPT-1W leads. Cable connectors supplied.	30" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Includes 8" slotted in-ground stake and 50W(VA) Q50T4 (17015), Halogen light source.	Includes 8" slotted in-ground stake. Brass will naturally patina over time.
Accessories	<p><b>Mounting:</b>  <b>15601</b> Surface Mounting Flange  <b>15607</b> Surface Mounting Bracket  <b>15609</b> Junction Box Mounting Bracket</p>	<p><b>15647</b> 90° Elbow  <b>15649</b> Stem Coupler  <b>15645, 15656, 15657, 15658, 15570</b> Stems</p>
Dimensions		