



	MR16 Downlight	MR16 Mini Downlight
Finishes	<b>CBR</b>	<b>AZT</b>
Item Number and Finish	<b>15486 CBR</b>	<b>15087 AZT</b>
Housing	Cast Brass	Cast Aluminum with stainless steel screen
Lamp Base	12V Bi-Pin, high-temperature porcelain socket	
Lamp Options-Power Usage at 12V AC input	<b>LED Only:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen	<b>Incandescent:</b> 50W(VA) MR16 20W(VA) Max. Canada 35W(VA) MR11  <b>LED:</b> 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen
Wiring	30" of usable #18-2, SPT-1W leads. Cable connectors supplied.	35" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Includes 8" slotted in-ground stake and Surface Mounting Bracket <b>15516CBR</b> . For downlight use only.	Includes Surface Mounting Bracket <b>15607</b> . For downlight use only.
Accessories	<b>Mounting:</b> <b>15489CBR</b> Gutter Mount <b>15609</b> Junction Box Mounting Bracket	<b>Mounting:</b> <b>15601</b> Surface Mounting Flange <b>15609</b> Junction Box Mounting Bracket
Dimensions		