





	Solid Brass In-Ground	PAR36 Well
Finishes	<b>CBR</b>	<b>BK</b>
Item Number and Finish	<b>15481</b> CBR	<b>15088</b> BK <b>15088</b> BK 12 - bulk packed in 12 (Yoke Held) <b>15488</b> BK 12 - bulk packed in 12 (Rubber Boot)
Housing	Cast Brass with heat-resistant frosted lens	Stainless steel gimble ring with silicone rubber lamp support clips. Heavy-duty polycarbonate ground support sleeve.
Lamp Base	12V Bi-Pin, high-temperature porcelain socket	12V PAR36 screw terminal
Lamp Options-Power Usage at 12V AC input	<b>LED only:</b> 4W PAR36 (18126-18133) Compares up to 20W Halogen 5W PAR36 (18134-18141) Compares up to 35W Halogen 7W PAR36 (18142-18149) Compares up to 50W Halogen	<b>LED only:</b> 4W PAR36 (18166-18173) Compares up to 20W Halogen 6W PAR36 (18174-18181) Compares up to 35W Halogen 10W PAR36 (18182-18189) Compares up to 50W Halogen 11W PAR36 (18021-18028) Compares up to 50W Halogen 14W PAR36 (18190-18197) Compares up to 75W Halogen
Wiring	34" of usable #18-2, SPT-1W leads. Cable connectors are not included.	42" of usable #18-2, SPT-1W leads. Cable connectors supplied. Supply wire with lugs attach directly to PAR36 light bulb screw terminals.
Notes	Can be installed in concrete and is drive-over and walk-over rated. Includes composite installation sleeve (shown in image above). Brass will naturally patina over time.	Versatile design with reversible support sleeve to accommodate uplighting when flush mounted or angled lighting effects when semi-recessed. Stainless steel gimble ring design holds lamp securely at desired angle.
Accessories	<b>Lens:</b> <b>15482</b> CBR Rock Guard with Clear Lens 	<b>Lens:</b> <b>15689</b> BK Lens Cover  <b>15690</b> BK Rock Guard
Dimensions	