



	MR16 Mini In-Ground with Cowl	MR16 Well
Finishes	BK	BKT
Item Number and Finish	15192 BK	15092 BKT
Housing	Components of durable high heat thermo-plastic composite resin. Glare shield molded into lid. Light bulb shielded by a heat-resistant convex shaped glass lens for better debris run-off. Fully sealed for watertight outdoor usage.	Aluminum housing with heat-resistant flat glass lens is fully sealed. Heavy-duty polypropylene sleeve provides in-ground fixture support.
Lamp Base	12V Bi-Pin, high-temperature porcelain socket	
Lamp Options-Power Usage at 12V AC input	<p>Incandescent: VA Max: 50W(VA) 50W(VA) MR16 10W(VA) Max. Canada 35W(VA) Max. MR11</p> <p>LED: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen</p>	<p>Incandescent: VA Max: 50W(VA) 50W(VA) MR16</p> <p>LED: 4W MR16 (18126-18133) Compares up to 20W Halogen 5W MR16 (18134-18141) Compares up to 35W Halogen 7W MR16 (18142-18149) Compares up to 50W Halogen</p>
Wiring	36" of usable #18-2, SPT-1W leads. Cable connectors supplied.	36" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Same as 15190 with added glare shield for optimal viewing comfort. Recommended for salt-air environments.	
Accessories		<p>Lens: 15675 LIN Linear Lens 15676 FRO Frosted Lens 15679 BK Hexcell Louver Shield 15686 BL Blue Lens</p>
Dimensions		