

# Retrofit Path & Spread



	One Tier		Three Tier																																					
Finishes	<b>AZT</b>		<b>BKT (shown), AZT</b>																																					
Item Number and Finish	15011 AZT		15005 AZT 15005 BKT																																					
Housing	Cast Aluminum with molded ribbed diffuser of clear UV stabilized, high-impact resistant polycarbonate. <b>Mounting stems and bollard kits not included.</b>		Cast Aluminum with molded ribbed diffuser of clear UV stabilized, high-impact resistant polycarbonate. <b>Mounting stems and bollard kits not included.</b>																																					
Lamp Base	12V S8 Wedge base socket		12V S8 Wedge base socket																																					
Lamp Options-Power Usage at 12V AC input	<b>Incandescent:</b> 18.5W(VA) 3155K (15599 CLR)	<b>LED:</b> 2W S8 Wedge (18036, 18037) Compares up to 18.5W Krypton 2W S8 Wedge (18202, 18203) Compares up to 20W Halogen	<b>Incandescent:</b> 18.5W(VA) 3155K (15599 CLR)	<b>LED:</b> 2W S8 Wedge (18036, 18037) Compares up to 18.5W Krypton 2W S8 Wedge (18202, 18203) Compares up to 20W Halogen																																				
Wiring	52" of usable #18-2, SPT-1W leads. Cable connectors supplied.		52" of usable #18-2, SPT-1W leads. Cable connectors supplied.																																					
Notes	Includes 24.4W(VA) 3156K (15598 CLR) Krypton lamp. Stem mount not included. Available in stem mount, deck mount or as a bollard. Mounting stem and bollard kit sold separately. Photometrics given below with 18" stem.		Includes 24.4W(VA) 3156K (15598 CLR) Krypton lamp. Stem mount not included. Available in stem mount, deck mount or as a bollard. Mounting stem and bollard kit sold separately. Photometrics given below with 18" stem.																																					
Accessories	15656, 15657, 15658 or 15570 Stems 15575, 15576 or 15578 Stakes 15665, 15666 or 15667 Bollard 15671 ST Bollard Template Kit		15601 Surface Mounting Flange 15602 Flange Mounting Nipple 15607 Surface Mounting Bracket																																					
Dimensions																																								
Photometrics*	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>5.3</td><td>1.8</td><td>.9</td><td>.68</td><td>.13</td><td>-</td><td>-</td><td>-</td> </tr> </table>		Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	5.3	1.8	.9	.68	.13	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>1.8</td><td>.73</td><td>.4</td><td>.27</td><td>.3</td><td>-</td><td>-</td><td>-</td> </tr> </table>		Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	1.8	.73	.4	.27	.3	-	-	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	5.3	1.8	.9	.68	.13	-	-	-																																
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	1.8	.73	.4	.27	.3	-	-	-																																