



	Fundamentals™		Ribbed Roof
Finishes	TZT (shown), CO, OB		AZT
Item Number and Finish	15439 CO 15439 OB 15439 TZT		15418 AZT
Housing	Brass or Copper (CO)		Cast Aluminum with clear glass sprinkler shield
Lamp Base	12V S8 Wedge base socket		12V T3 Bi-Pin, high-temperature porcelain socket
Lamp Options-Power Usage at 12V AC input	Incandescent: 18.5W(VA) 3155K (15599 CLR)	LED: 2W S8 Wedge (18036, 18037) Compares up to 18.5W Krypton 2W S8 Wedge (18202, 18203) Compares up to 20W Halogen	Incandescent: 10W(VA) T3 (17011) LED: 2W G4/T3 (18042, 18043) Compares up to 20W Halogen 1.2W T3/G4 (18200, 18201) Compares up to 10W Halogen 2W T3/G4 (18206, 18207) Compares up to 20W Halogen
Wiring	35" of usable #18-2, SPT-1W leads. Cable connectors supplied.		20" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Includes 24.4W(VA) 3156K (15598 CLR) Krypton lamp and 8" in-ground slotted stake. LED version of fixture 15839 on page 45. Brass and Copper will naturally patina over time.		Includes 20W(VA) T3 (17012) Halogen lamp and 8" in-ground slotted stake.
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket		
Dimensions			
Photometrics*			
Distance from Light	1' 2' 3' 4' 5' 6' 7' 8'		1' 2' 3' 4' 5' 6' 7' 8'
Footcandles	13.4 4.55 1.65 .58 .13 - - -		11.7 5.4 1.1 .2 - - - -

*Values stated for supplied lamp with fixture.