



	Mica Mission	Thatched Roof																																				
Finishes	TZT	TZT																																				
Item Number and Finish	15450 TZT	15401 AZT																																				
Housing	Cast Aluminum with Mica finished glass panels	Cast Aluminum with clear glass sprinkler shield																																				
Lamp Base	12V T5 Wedge base socket	12V T3 Bi-Pin, high-temperature porcelain socket																																				
Lamp Options-Power Usage at 12V AC input	<p>Incandescent: 16.25W(VA) 921X (17025) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021)</p> <p>LED: 1.2W T5 Wedge (18198, 18199) Compares up to 10W Halogen 2W T5 Wedge (18204, 18205) Compares up to 20W Halogen</p>	<p>Incandescent: 10W(VA) T3 (17011)</p> <p>LED: 2W G4/T3 (18042, 18043) Compares up to 20W Halogen 1.2W T3/G4 (18200, 18201) Compares up to 10W Halogen 2W T3/G4 (18206, 18207) Compares up to 20W Halogen</p>																																				
Wiring	22" of usable #18-2, SPT-1W leads. Cable connectors supplied.	20" of usable #18-2, SPT-1W leads. Cable connectors supplied.																																				
Notes	Includes 11.6W(VA) 912X (17023) Xenon lamp and 8" in-ground slotted stake.	Includes 20W(VA) T3 (17012) Halogen lamp and 8" in-ground slotted stake.																																				
Accessories	<p>15601 Surface Mounting Flange 15607 Surface Mounting Bracket</p>																																					
Dimensions																																						
Photometrics*	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>1.34</td> <td>1.61</td> <td>1.63</td> <td>.86</td> <td>.46</td> <td>.07</td> <td>.07</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	1.34	1.61	1.63	.86	.46	.07	.07	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>1.34</td> <td>1.61</td> <td>1.63</td> <td>.86</td> <td>.46</td> <td>.07</td> <td>.07</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	1.34	1.61	1.63	.86	.46	.07	.07	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	1.34	1.61	1.63	.86	.46	.07	.07	-																														
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	1.34	1.61	1.63	.86	.46	.07	.07	-																														

*Values stated for supplied lamp with fixture.