



	Pierced Dome		Pierced Scrollwork																																					
Finishes	AZT		TZT																																					
Item Number and Finish	15457 AZT		15437 TZT																																					
Housing	Cast Aluminum		Cast Aluminum																																					
Lamp Base	12V T5 Wedge base socket		12V T5 Wedge base socket																																					
Lamp Options-Power Usage at 12V AC input	<b>Incandescent:</b> 11.6W(VA) 912X (17023) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021)	<b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 1.2W T5 Wedge (18198, 18199) Compares up to 10W Halogen 2W T5 Wedge (18204, 18205) Compares up to 20W Halogen	<b>Incandescent:</b> 11.6W(VA) 912X (17023) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021)	<b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 1.2W T5 Wedge (18198, 18199) Compares up to 10W Halogen 2W T5 Wedge (18204, 18205) Compares up to 20W Halogen																																				
Wiring	24" of usable #18-2, SPT-1W leads. Cable connectors supplied.		24" of usable #18-2, SPT-1W leads. Cable connectors supplied.																																					
Notes	Includes 16.25W(VA) 921X (17025) Xenon lamp and 8" in-ground slotted stake. Features decorative light-leak pattern. LED version of fixture <b>15857</b> on page 57.		Includes 16.25W(VA) 921X (17025) Xenon lamp and 8" in-ground slotted stake. Features decorative light-leak pattern. Fixture head is square in shape.																																					
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket																																							
Dimensions																																								
Photometrics*	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>5.22</td> <td>3.76</td> <td>2.02</td> <td>.89</td> <td>.12</td> <td>.05</td> <td>-</td> <td>-</td> </tr> </table>		Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	5.22	3.76	2.02	.89	.12	.05	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>6.99</td> <td>3.14</td> <td>1.56</td> <td>.44</td> <td>.1</td> <td>.05</td> <td>.03</td> <td>-</td> </tr> </table>		Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	6.99	3.14	1.56	.44	.1	.05	.03	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	5.22	3.76	2.02	.89	.12	.05	-	-																																
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	6.99	3.14	1.56	.44	.1	.05	.03	-																																

\*Values stated for supplied lamp with fixture.