

# Retrofit Path & Spread



	Cross Creek™ Lantern	Intaglio Brass Crook Neck																																				
Finishes	<b>AGZ</b>	<b>OZ</b>																																				
Item Number and Finish	<b>15322 AGZ</b>	<b>15436 OZ</b>																																				
Housing	Cast Aluminum with textured amber linen seedy glass panels	Brass																																				
Lamp Base	12V T5 Wedge base socket	12V T5 Wedge base socket																																				
Lamp Options-Power Usage at 12V AC input	<b>Incandescent:</b> 11.6W(VA) 912X (17023) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021)	<b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 2W T5 Wedge (18204, 18205) Compares up to 20W Halogen																																				
	<b>Incandescent:</b> 16.25W(VA) 921X (17025) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021)	<b>LED:</b> 1.2W T5 Wedge (18198, 18199) Compares up to 10W Halogen 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 2W T5 Wedge (18204, 18205) Compares up to 20W Halogen																																				
Wiring	35" of usable #18-2, SPT-1W leads. Cable connectors supplied.	26" of usable #18-2, SPT-1W leads. Cable connectors supplied.																																				
Notes	Includes 16.25W(VA) 921X (17025) Xenon lamp and 8" in-ground slotted stake. U.S. Patent No. D580,084.	Includes 11.6W(VA) 912X (17023) Xenon lamp and 8" in-ground slotted stake. Etched floral pattern on brass shade. Brass will naturally patina over time.																																				
Accessories	<b>15601</b> Surface Mounting Flange <b>15607</b> Surface Mounting Bracket																																					
Dimensions																																						
Photometrics*	<table border="1"> <tr> <th>Distance from Light</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> </tr> <tr> <td>Footcandles</td> <td>1.2</td> <td>.26</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	1.2	.26	-	-	-	-	-	-	<table border="1"> <tr> <th>Distance from Light</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> </tr> <tr> <td>Footcandles</td> <td>5.03</td> <td>3.18</td> <td>1.45</td> <td>.68</td> <td>.3</td> <td>.13</td> <td>.03</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	5.03	3.18	1.45	.68	.3	.13	.03	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	1.2	.26	-	-	-	-	-	-																														
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	5.03	3.18	1.45	.68	.3	.13	.03	-																														