

Retrofit Path & Spread



	Tulip	Adjustable Crescent																																				
Finishes	MST	OZ																																				
Item Number and Finish	15349 MST	15330 OZ																																				
Housing	Aluminum	Brass																																				
Lamp Base	12V S8 Wedge base socket	12V S8 Wedge base socket																																				
Lamp Options-Power Usage at 12V AC input	Incandescent: 18.5W(VA) 3155K (15599 CLR) LED: 2W S8 Wedge (18036, 18037) Compares up to 18.5W Krypton	Incandescent: 18.5W(VA) 3155K (15599 CLR) LED: 2W S8 Wedge (18036, 18037) Compares up to 18.5W Krypton 2W S8 Wedge (18122, 18123) Compares up to 18.5W Krypton																																				
Wiring	37" of usable #18-2, SPT-1W leads. Cable connectors supplied.	42" of usable #18-2, SPT-1W leads. Cable connectors supplied.																																				
Notes	Includes 18.5W(VA) 3155K (15599 CLR) Krypton lamp and 8" in-ground slotted stake.	Includes 24.4W(VA) 3156K (15598 CLR) Krypton lamp and 8" in-ground slotted stake. Adjustable shade on this versatile fixture allows it to be used as a path light, accent light or for wall washing. Brass will naturally patina over time.																																				
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket																																					
Dimensions																																						
Photometrics*	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>12.7</td> <td>4.1</td> <td>1</td> <td>.2</td> <td>.07</td> <td>.02</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	12.7	4.1	1	.2	.07	.02	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>9.98</td> <td>4.13</td> <td>1.52</td> <td>.6</td> <td>.22</td> <td>.03</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	9.98	4.13	1.52	.6	.22	.03	-	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	12.7	4.1	1	.2	.07	.02	-	-																														
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'																														
Footcandles	9.98	4.13	1.52	.6	.22	.03	-	-																														