





	Mission Bollard	Zen Garden Bollard	Cathedral™ Bollard
Finishes	<b>OZ</b>	<b>OZ</b>	<b>TZT</b>
Item Number and Finish	15458 OZ	15392 OZ	15449 TZT
Housing	Brass with honey beige glass	Brass with textured amber seedy linen glass	Aluminum with dark citrine glass
Lamp Base	12V T5 Wedge base socket	12V T5 Wedge base socket	12V T5 Wedge base socket
Lamp Options- Power Usage at 12V AC input	<b>Incandescent:</b> 16.25W(VA) 921X (17025) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021) <b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 1.2W T3/G4 (18200, 18201) Compares up to 10W Halogen 2W T3/G4 (18206, 18207) Compares up to 20W Halogen	<b>Incandescent:</b> 16.25W(VA) 921X (17025) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021) <b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 1.2W T3/G4 (18200, 18201) Compares up to 10W Halogen 2W T3/G4 (18206, 18207) Compares up to 20W Halogen	<b>Incandescent:</b> 16.25W(VA) 921X (17025) 6.5W(VA) 918X (17022) 4W(VA) 901X (17021) <b>LED:</b> 2W T5 Wedge (18039, 18040) Compares up to 16W Xenon 1.2W T3/G4 (18200, 18201) Compares up to 10W Halogen 2W T3/G4 (18206, 18207) Compares up to 20W Halogen
Wiring	22" of usable #18-2, SPT-1W leads. Cable connectors supplied.	35" of usable #18-2, SPT-1W leads. Cable connectors supplied.	22" of usable #18-2, SPT-1W leads. Cable connectors supplied. <b>Coordinating Product</b>
Notes	Includes 11.6W(VA) 912X (17023) Xenon lamp and 8" in-ground slotted stake. Brass will naturally patina over time.	Includes 11.6W(VA) 912X (17023) Xenon lamp and 8" in-ground slotted stake. Brass will naturally patina over time.	Includes 11.6W(VA) 912X (17023) Xenon lamp and 8" in-ground slotted stake.  Path Light 15391, see page 148  Path Light 15429, see page 149
Accessories	15601 Surface Mounting Flange, 15607 Surface Mounting Bracket		
Dimensions			
Photometrics*			
Distance from Light	1' 2' 3' 4' 5' 6' 7' 8'	1' 2' 3' 4' 5' 6' 7' 8'	1' 2' 3' 4' 5' 6' 7' 8'
Footcandles	5.3 2.1 .5 .02 - - - -	.36 .2 - - - - -	1.81 1.26 .7 .39 .25 .16 .012 .01

\*Values stated for supplied lamp with fixture.