



	Up/Down Accent Deck Light AZT	Barbecue Light BK
Finishes		
Item Number and Finish	15079 AZT	15123 BK
Housing	Aluminum	Components of durable, high-heat, thermo-plastic resin. Lamp shielded by a high-heat resistant flat glass lens sealed for watertight outdoor use. Flexible stem is durable chrome-plated steel with heat shrink rubber sleeving. On/off switch is protected by waterproof rubber boot.
Lamp Base	12V T5 Wedge base socket	12V Bi-Pin, high-temperature porcelain socket
Lamp Options-Power usage at 12V AC input	Incandescent: 4W(VA) 901X (17021) 6.5W(VA) 918X (17022) LED: 1.2W T5 Wedge (18198, 18199) Compares up to 10W Halogen	LED only: 2.5W MR11 (18158-18165)
Wiring	70" of usable #18-2, SPT-1W leads. Cable connectors supplied.	25" of usable #18-2, SPT-1W leads. Cable connectors supplied.
Notes	Includes stainless steel surface mounting plate and two 11.6W(VA) 912X (17023) Xenon lamps.	Includes one set of wood screws, one set of machine screws and nuts. For rail or outdoor countertop mount only.
Accessories	15659 AZT Heat-Resistant Lens	
Dimensions	<p>Diagram showing the dimensions of the Up/Down Accent Deck Light (AZT). The height is 6", the width is 3", and the depth of the cylindrical body is 2.25".</p>	<p>Diagram showing the dimensions of the Barbecue Light (BK). The height of the base is 6", and the total height including the flexible gooseneck is 24".</p>