

Retrofit Deck & Patio



	Louvered Brick Light	Acrylic Lens Brick Light
Finishes	AZT	AZT
Item Number and Finish	15073 AZT	15074 AZT
Housing	Cast Aluminum with a fully sealed, heat-resistant glass lens	Cast Aluminum with a fully sealed, heat-resistant glass lens
Lamp Base	(2) 12V T3 Bi-Pin, high-temperature porcelain sockets	(2) 12V T3 Bi-Pin, high-temperature porcelain sockets
Lamp Options-Power usage at 12V AC input	LED only: 2W T3/G4 Bi-Pin (18042, 18043) Compares up to 20W Halogen 1.2W T3/G4 Bi-Pin (18200, 18201) Compares up to 10W Halogen 2W T3/G4 Bi-Pin (18206, 18207) <i>Light distribution may be affected by location of sockets</i>	LED only: 2W T3/G4 Bi-Pin (18042, 18043) Compares up to 20W Halogen 1.2W T3/G4 Bi-Pin (18200, 18201) Compares up to 10W Halogen 2W T3/G4 Bi-Pin (18206, 18207) <i>Light distribution may be affected by location of sockets</i>
Wiring	Wire connection must be made inside fixture housing. 75° supply wire required.	Wire connection must be made inside fixture housing. 75° supply wire required.
Notes	Includes stainless steel mounting bracket and two 10W(VA) Q10T3 (17011) Halogen lamps. LED version of fixture 15773 on page 68. For masonry or concrete use, outdoors only.	Included stainless steel mounting hardware and junction box. Designed to be integrated into brick wall during construction. LED version is also usable in vertical risers. LED version of fixture 15774 on page 68.
Dimensions		