

C-Series Accent



	Small Accent – 5.3W		Small Accent – 10W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K – Pure White	4000K – Cool White	3000K – Pure White	4000K – Cool White
Item Number by Beam Spread and Finish	15° Beam Spread 16209 AZT30 16209 BKT30	15° Beam Spread 16209 AZT40 16209 BKT40	15° Beam Spread 16212 AZT30 16212 BKT30	15° Beam Spread 16212 AZT40 16212 BKT40
	40° Beam Spread 16210 AZT30 16210 BKT30	40° Beam Spread 16210 AZT40 16210 BKT40	40° Beam Spread 16213 AZT30 16213 BKT30	40° Beam Spread 16213 AZT40 16213 BKT40
	55° Beam Spread 16211 AZT30 16211 BKT30	55° Beam Spread 16211 AZT40 16211 BKT40	55° Beam Spread 16214 AZT30 16214 BKT30	55° Beam Spread 16214 AZT40 16214 BKT40
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	5.3W, .9pf 478 lm, 93 lm/W	5.3W, .9pf 514 lm, 100 lm/W	10W, .9pf 831 lm, 82 lm/W	10W, .9pf 942 lm, 91 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV.			
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Notes	Replaces the equivalent of a 35W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed. Photometrics on page 218.		Replaces the equivalent of a 50W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed. Photometrics on page 218.	
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15645, 15656, 15657, 15658 Stems			
Dimensions				