



	Large Accent – 14.3W		Large Accent – 21W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K - Pure White	4000K - Cool White	3000K - Pure White	4000K - Cool White
Item Number by Beam Spread and Finish	15° Beam Spread 16215 AZT30 16215 BKT30	15° Beam Spread 16215 AZT40 16215 BKT40	15° Beam Spread 16218 AZT30 16218 BKT30	15° Beam Spread 16218 AZT40 16218 BKT40
	33° Beam Spread 16216 AZT30 16216 BKT30	33° Beam Spread 16216 AZT40 16216 BKT40	33° Beam Spread 16219 AZT30 16219 BKT30	33° Beam Spread 16219 AZT40 16219 BKT40
	55° Beam Spread 16217 AZT30 16217 BKT30	55° Beam Spread 16217 AZT40 16217 BKT40	55° Beam Spread 16220 AZT30 16220 BKT30	55° Beam Spread 16220 AZT40 16220 BKT40
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	14W, .9pf 1263 lm, 90 lm/W	14W, .9pf 1374 lm, 96 lm/W	21W, .9pf 2015 lm, 97 lm/W	21W, .9pf 2111 lm, 99 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV.			
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Notes	Replaces the equivalent of a 90W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed. Photometrics on page 218.		Replaces the equivalent of a 35W Metal Halide. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed. Photometrics on page 218.	
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15645, 15656, 15657, 15658 Stems			
Dimensions				