

Accent



	Small Accent – 12.5W				Large Accent – 19.5W			
Finish	BBR				BBR			
Color Temperature	3000K - Pure White		4250K - Cool White		3000K - Pure White		4250K - Cool White	
Item Number by Beam Spread and Finish	10° Beam Spread 16200 BBR30		10° Beam Spread 16200 BBR40		10° Beam Spread 16202 BBR30		10° Beam Spread 16202 BBR40	
	35° Beam Spread 16201 BBR30		35° Beam Spread 16201 BBR40		35° Beam Spread 16203 BBR30		35° Beam Spread 16203 BBR40	
	60° Beam Spread 16206 BBR30		60° Beam Spread 16206 BBR40		60° Beam Spread 16207 BBR30		60° Beam Spread 16207 BBR40	
Housing	Cast Brass				Cast Brass			
Wattage/VA, Delivered Lumens & Efficacy	12.5W .13VA, .85pf	590 lm 47 lm/W	12.5W .13VA, .85pf	646 lm 52 lm/W	19.5W .18VA, .90pf	947 lm 49 lm/W	19.5W .18VA, .90pf	993 lm 51 lm/W
CRI	80+				80+			
Voltage Range	108V-132V, 50-60Hz. Surge protection up to 4kV.							
Light Source	5 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.				8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Notes	Replaces the equivalent of a 50W Halogen. IP66 rated. Brass will naturally patina over time.				Replaces the equivalent of a 75W Halogen. IP66 rated. Brass will naturally patina over time.			
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15645, 15656, 15657, 15658 Stems							
Dimensions								