



**Large Accent – 29W**

Finish	<b>BBR</b>			
Color Temperature	3000K - Pure White		4250K - Cool White	
Item Number by Beam Spread and Finish	<b>10° Beam Spread</b> <b>16204 BBR30</b>  <b>35° Beam Spread</b> <b>16205 BBR30</b>  <b>60° Beam Spread</b> <b>16208 BBR30</b>		<b>10° Beam Spread</b> <b>16204 BBR40</b>  <b>35° Beam Spread</b> <b>16205 BBR40</b>  <b>60° Beam Spread</b> <b>16208 BBR40</b>	
Housing	Cast Brass			
Wattage/VA, Delivered Lumens & Efficacy	29W .27VA, .90pf	1131 lm 39 lm/W	29W .27VA, .90pf	1368 lm 47 lm/W
CRI	80+			
Voltage Range	108V-132V, 50-60Hz. Surge protection up to 4kV.			
Light Source	8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Notes	Replaces the equivalent of a 100W Halogen. IP66 rated. Brass will naturally patina over time.			
Accessories	<b>15276</b> Power Post® <b>15601</b> Surface Mounting Flange <b>15609</b> Junction Box Mounting Bracket <b>15645, 15656, 15657, 15658</b> Stems			
Dimensions				