



	Medium Flood – 33.5W		Medium Flood – 52W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K - Pure White	4000K - Cool White	3000K - Pure White	4000K - Cool White
Item Number by Mounting Type and Finish	Knuckle Mount: 16223 AZT30 16223 BKT30	Knuckle Mount: 16223 AZT40 16223 BKT40	Knuckle Mount: 16224 AZT30 16224 BKT30	Knuckle Mount: 16224 AZT40 16224 BKT40
	Trunnion Mount: 16223 AZT30TR 16223 BKT30TR	Trunnion Mount: 16223 AZT40TR 16223 BKT40TR	Trunnion Mount: 16224 AZT30TR 16224 BKT30TR	Trunnion Mount: 16224 AZT40TR 16224 BKT40TR
	Slip-Fit Mount: 16223 AZT30SL 16223 BKT30SL	Slip-Fit Mount: 16223 AZT40SL 16223 BKT40SL	Slip-Fit Mount: 16224 AZT30SL 16224 BKT30SL	Slip-Fit Mount: 16224 AZT40SL 16224 BKT40SL
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	33W, .9pf 3285 lm, 99 lm/W	33W, .9pf 3495 lm, 104 lm/W	50W, .9pf 4496 lm, 89 lm/W	50W, .9pf 4795 lm, 92 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV		120V-277V, 50-60Hz. Surge protection up to 4kV	
Light Source	2 integrated high-output LEDs with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Notes	Replaces the equivalent of a 70W Metal Halide. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal proof hardware installed. Photometrics on page 218.		Replaces the equivalent of a 100W Metal Halide. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal proof hardware installed. Photometrics on page 218.	
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15656, 15657, 15658 Stems			

Dimensions

