

# Outdoor Wall Lights



	Outdoor Up & Down Lantern		Outdoor Lantern							
Finishes	<b>BKT (shown), AZT</b>		<b>AZT (shown), BKT</b>		Additional Finishes					
Color Temperature	3000K - Pure White		3000K - Pure White		 <b>BKT</b>					
Item Number and Finish	<b>11251 AZT30</b> <b>11251 BKT30</b>		<b>11250 AZT30</b> <b>11250 BKT30</b>							
Housing	Cast Aluminum with powder coat finish and polycarbonate top shield		Cast Aluminum with powder coat finish							
Power Usage at 120V AC Input VA and Watts	15W		11W							
CRI	90+		90+							
	<b>AZT</b>		<b>BKT</b>							
Voltage Range	120V-277V AC, 50-60 Hz			120V-277V AC, 50-60 Hz						
Light Source	Integrated high-output LEDs and drivers. Tested to a Lumen Maintenance L70 of 40,000 hrs.			Integrated high-output LEDs and drivers. Tested to a Lumen Maintenance L70 of 40,000 hrs.						
Delivered Lumens & Efficacy	550 lm	37 lm/W	350 lm	32 lm/W						
Wiring	8" of usable 105°C, 18 AWG wire leads			8" of usable 105°C, 18 AWG wire leads						
Notes	Energy-efficient			Perfect for Dark Sky applications and energy-efficient.						
Dimensions										
Photometrics										
Distance from Light (ft.)	4.2'	8.4'	12.5'	16.7'	20.9'	4'	8.3'	12.4'	16.5'	20.6'
Foot-candles	52.1	13	5.8	3.3	2.1	50.9	12.7	5.7	3.2	2