

Retrofit Path & Spread



	Three Tier		Large One Tier	
Finishes	BKT (shown), AZT		AZT (shown), BKT	
Item Number and Finish	15205 AZT 15205 BKT		15211 AZT 15211 BKT	
Housing	Cast Aluminum with molded ribbed diffuser of clear UV stabilized high-impact resistant polycarbonate. Mounting stems and bollard kits not included.		Cast Aluminum with molded ribbed diffuser of clear UV stabilized high-impact resistant polycarbonate. Mounting stems and bollard kits not included.	
Lamp Base	120V medium base porcelain socket with nickel plated screw shell		4000V (4KV) pulse rated medium base porcelain socket	
Lamp Options-Power usage at 120V AC input	Incandescent: 75W Max. A19 lamp	LED: A19 Damp Location	Incandescent: Internal ANSI M98 Metal Halide ballast with 120V tap	LED: A19 Damp Location
Wiring	30" of usable 105°C, #18 AWG wire leads		30" of usable 105°C, #18 AWG wire leads	
Notes	Available as stem mount, deck mount or as a bollard. Mounting stems and bollard kits sold separately.		Available as stem mount, deck mount or as a bollard. Mounting stems and bollard kits sold separately.	
Accessories	15645, 15656, 15657 or 15658 Stems 15276 BK Power Post® 15665, 15666 or 15667 Bollard Mounting Kits 15578 Bollard Mounting Stakes		15671 Bollard Template Kit 15601 Surface Mounting Flange (needed for attachment to junction box) 15602 AL Flange Mounting Nipple 15616WH10 Gel Encapsulant 10 pack	
Dimensions				