

Photometrics: 120V-277V Integrated LED C-Series

120V-277V Integrated LED Accent - Small													
Item Number	16209		16210		16211		16212		16213		16214		
Beam Angle	15° Spot		40° Flood		55° Wide Flood		15° Spot		40° Flood		55° Wide Flood		
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	
3.3'	172	1	79.4	2.1	41.1	3.4	321.3	1	137	2.1	76.4	3.3	
6.6'	43	1.9	19.9	4.3	10.3	6.8	80.3	1.9	34.3	4.3	19.1	6.5	
9.8'	19	2.9	8.8	6.4	4.6	10.2	35.7	2.9	15.2	6.4	8.5	9.8	
13.1'	10.8	3.8	5	8.5	2.6	13.6	20.1	3.8	8.6	8.6	4.8	13.1	
16.4'	6.9	4.8	3.2	10.6	1.6	17	12.9	4.8	5.5	10.7	3.1	16.3	
19.7'	4.8	5.8	2.2	12.8	1.1	20.3	8.9	5.7	3.8	12.9	2.1	19.6	
23'	3.5	6.8	1.6	14.9	.8	23.7	6.6	6.7	2.8	15	1.6	22.9	
26.3'	2.7	7.7	1.2	17	.6	27.1	5	7.6	2.1	17.2	1.2	26.1	
29.5'	2.1	8.7	1	19.1	.5	30.5	4	8.6	1.7	19.3	1	29.4	
32.8'	1.7	9.7	.8	21.3	.4	33.9	3.2	9.5	1.4	21.5	.8	32.7	

120V-277V Integrated LED Accent - Large													
Item Number	16215		16216		16217		16218		16219		16220		
Beam Angle	15° Spot		33° Flood		55° Wide Flood		15° Spot		33° Flood		55° Wide Flood		
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	
3.3'	967.7	.7	244	1.7	115.4	3.3	924.2	.9	324.2	2	165.9	3.2	
6.6'	241.9	1.3	61	3.4	28.9	6.5	231	1.7	81.1	4	41.5	6.4	
9.8'	107.5	2	27.1	5.2	12.8	9.7	102.7	2.6	36	6	18.4	9.7	
13.1'	60.5	2.7	15.2	6.9	7.2	13	57.8	3.5	20.3	8	10.4	12.9	
16.4'	38.7	3.4	9.8	8.6	4.6	16.3	37	4.3	13	10	6.6	16.1	
19.7'	26.9	4	6.8	10.3	3.2	19.5	25.7	5.2	9	12	4.6	19.3	
23'	19.8	4.7	5	12	2.4	22.8	18.9	6.1	6.6	14	3.4	22.5	
26.3'	15.1	5.4	3.8	13.7	1.8	26	14.4	6.9	5.1	16	2.6	25.7	
29.5'	12	6	3	15.5	1.4	29.3	11.4	7.8	4	18	2	29	
32.8'	9.7	6.7	2.4	17.2	1.2	32.5	9.2	8.7	3.2	20	1.7	32.2	

120V-277V Integrated LED Flood											
Item Number	16221 - Small		16222 - Small		16223 - Medium		16224 - Medium		16225 - Large		
Beam Angle	NEMA 6x5		NEMA 6x5		NEMA 7x5		NEMA 7x5		NEMA 7x6		
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	
3.3'	37.1	4.9	70.8	4.6	129.7	4	171.6	4.2	155	6.6	
6.6'	9.3	9.8	17.7	9.3	32.4	8.2	42.9	8.4	38.7	13.2	
9.8'	4.1	14.7	7.9	14	14.4	12.2	19.1	12.6	17.2	19.8	
13.1'	2.3	19.6	4.4	18.6	8.1	16.3	10.7	16.8	9.7	26.5	
16.4'	1.5	24.5	2.8	23.2	5.2	20.4	6.9	21	6.2	33	
19.7'	1	29.4	2	27.9	3.6	24.5	4.8	25.2	4.3	39.7	
23'	.8	34.3	1.4	32.5	2.6	28.5	3.5	29.4	3.2	46.3	
26.3'	.6	39.2	1.1	37.2	2	32.6	2.7	33.6	2.4	52.9	
29.5'	.5	44.1	.9	41.8	1.6	36.7	2.1	37.8	1.9	59.5	
32.8'	.4	49	.7	46.5	1.3	40.8	1.7	42	1.6	66.1	

All Foot-candle values shown for 3000K color temperature.