

Photometrics: 120V Integrated LED Accent

120V Integrated LED Accent												
Item Number	16200		16202		16204		16201		16203		16205	
Beam Angle	10° Spot		10° Spot		10° Spot		35° Flood		35° Flood		35° Flood	
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width
8'	238.9	1.4	313.3	1.6	394.5	1.6	112.6	2.3	153.2	2.5	205.8	2.4
12'	106.2	2.1	139.2	2.4	175.3	2.5	28.1	4.5	38.3	4.9	51.5	4.8
24'	26.5	4.1	34.8	4.9	43.8	4.9	7	9	9.6	9.9	13.2	9.6
36'	11.8	6.2	15.5	7.3	19.5	7.4	3.1	13.6	4.3	14.8	5.9	14.4
48'	6.6	8.3	8.7	9.7	11	9.8	1.8	18.1	2.4	19.8	3.3	19.2
60'	4.2	10.3	5.6	12.1	7	12.3	1.1	22.6	1.5	24.7	2.1	24

Item Number	16206		16207		16208	
Beam Angle	60° Wide Flood		60° Wide Flood		60° Wide Flood	
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width
8'	26	4.2	43.4	4.1	53.5	4.2
12'	6.5	8.4	10.8	8.1	13.4	8.3
24'	1.6	16.9	2.7	16.3	3.4	16.7
36'	.7	25.3	1.2	24.4	1.5	25
48'	.4	33.7	.7	32.6	.8	33.3
60'	.3	42.4	.4	40.7	.5	41.6

Foot-candle values shown for 4250K color temperature.