

# Photometrics: 12V Integrated LED Accent

12V Integrated LED Accent									
Item Number	16150			16151			16152		
Beam Angle	10° Spot			35° Flood			60° Wide Flood		
Max Candela	3867			527			221		
Ft. Away	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	
8'	38.4	1.5	4'	21.7	2.5	4'	8.3	4.2	
12'	17.1	2.2	8'	5.4	4.9	8'	2.1	8.3	
24'	4.3	4.5	16'	1.4	9.8	16'	.5	16.7	
36'	1.9	6.7	24'	.6	14.7	24'	.2	25	
48'	1.1	8.9	32'	.3	19.6	32'	.1	33.3	
60'	.7	11.1	40'	.2	24.5	40'	.1	41.7	

  

12V Integrated LED Accent									
Item Number	16153			16154			16155		
Beam Angle	10° Spot			35° Flood			60° Wide Flood		
Max Candela	5213			738			282		
Ft. Away	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	
8'	66.2	1.5	4'	30.5	2.5	4'	10.7	4.3	
12'	29.4	2.3	8'	7.6	5	8'	2.7	8.7	
24'	7.4	4.6	16'	1.9	9.9	16'	.8	17.4	
36'	3.3	6.9	24'	.9	14.9	24'	.3	26.1	
48'	1.8	9.2	32'	.5	19.8	32'	.2	34.8	
60'	1.2	11.5	40'	.3	24.8	40'	.1	43.4	

  

12V Integrated LED Accent									
Item Number	16156			16157			16158		
Beam Angle	10° Spot			35° Flood			60° Wide Flood		
Max Candela	9236			1298			514.4		
Ft. Away	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	Ft.	Foot-candles	Beam Width	
8'	111	1.5	4'	54	2.4	4'	19.2	4.2	
12'	49.3	2.2	8'	13.5	4.8	8'	4.8	8.4	
24'	12.3	4.4	16'	3.4	9.7	16'	1.2	16.8	
36'	5.5	6.6	24'	1.5	14.5	24'	.5	25.2	
48'	3.1	8.7	32'	.8	19.3	32'	.3	33.6	
60'	2	10.9	40'	.5	24.2	40'	.2	42	

12V Integrated LED Water Accent			
Item Number	15711LED		
Beam Angle	60° Wide Flood		
Ft. Away	Foot-candles	Beam Width	
8'	5.6	3.3	
12'	1.5	6.5	
24'	.4	13	
36'	.2	19.5	
48'	.1	26	
60'	.1	32.5	

# Photometrics: 12V Integrated LED In-Ground

12V Integrated LED Well													
Item Number	15767		15728		15729		15768		15747		15757		
Beam Angle	10° Spot		10° Spot		10° Spot		35° Flood		35° Flood		35° Flood		
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	
8'	33.6	1.2	68.3	1.2	100.6	1.3	35.8	1.9	66.9	1.8	98.1	2.1	
12'	14.9	1.8	30.4	1.9	44.7	1.9	9	3.9	16.8	3.6	24.5	4.1	
24'	3.7	3.6	7.6	3.8	11.2	3.8	2.2	7.8	4.2	7.3	6.1	8.2	
36'	1.7	5.4	3.4	5.7	5	5.7	1	11.7	1.8	11	2.7	12.3	
48'	.9	7.2	1.9	7.6	2.8	7.6	.6	15.6	1	14.6	1.5	16.4	
60'	.6	9	1.2	9.5	1.8	9.5	.4	19.5	.7	18.3	1	20.5	