

Photometrics: 12V Integrated LED In-Ground

12V Integrated LED Well						
Item Number	15769		15748		15758	
Beam Angle	60° Wide Flood		60° Wide Flood		60° Wide Flood	
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width
8'	18.5	2.4	36.9	2.4	47	2.4
12'	4.7	4.8	9.3	4.8	11.8	4.8
24'	1.2	9.6	2.3	9.6	2.9	9.6
36'	.5	14.4	1	14.4	1.3	14.4
48'	.3	19.2	.6	19.2	.7	19.2
60'	.2	24	.4	24	.5	24

12V Integrated LED In-Ground												
Item Number	16030		16033		16036		16031		16034		16037	
Beam Angle	10° Spot		10° Spot		10° Spot		35° Flood		35° Flood		35° Flood	
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width
8'	32.6	1.6	113.8	1.4	214.7	1.4	21.7	2.3	53	2.4	98.5	2.3
12'	14.5	2.3	50.6	2.1	95.4	2	5.4	4.5	13.3	4.7	24.6	4.5
24'	3.6	4.7	12.6	4.3	23.8	4.1	1.4	9	3.3	9.4	6.1	9.1
36'	1.6	7	5.6	6.4	10.6	6.1	.6	13.5	1.5	14.1	2.7	13.6
48'	.9	9.3	3.2	8.6	6	8.1	.3	18	.8	18.9	1.5	18.1
60'	.6	11.7	2	10.7	3.8	10.1	.2	22.5	.5	23.6	1	22.6

Item Number	16032		16035		16038	
Beam Angle	60° Wide Flood		60° Wide Flood		60° Wide Flood	
Ft. Away	Foot-candles	Beam Width	Foot-candles	Beam Width	Foot-candles	Beam Width
8'	11.2	4.3	14.7	4.5	25.1	4.4
12'	2.8	8.6	3.7	9.1	6.3	8.8
24'	.7	17.3	.9	18.1	1.6	17.7
36'	.3	25.9	.4	27.2	.7	26.5
48'	.2	34.6	.2	36.2	.4	35.3
60'	.1	43.2	.1	45.3	.3	44.2

Photometrics: 12V Retrofit Accent with LED/Incandescent

