

INCLUDED FEATURES

- Blades (2) Included**
 - 28° Pitch
 - 54" Sweep
 - Non-reversible
 - ABS
- Downrods** Flush Mount Only
- Downlight** N/A
- Downlight Glass** N/A
- Optional Downlight** N/A
- Uplight** N/A
- Uplight Glass** N/A
- Low Ceiling Adaptable** No
- Control** 6-Speed DC Cooltouch™ Control System

FAN FEATURES

- Mounting Slope – Pitch** Flat ceiling only
- Lead Wire** 8"
- cETL Listed** Indoor
- Hanging Weight** 18.7 lbs.
- Body Material** Steel
- Warranty** Limited Lifetime

MOTOR FEATURES

- Motor Size/Type** DC-125
- Amps** 0.54 on High
- RPM** 132 on High
- Energy Star®** Yes

INCLUDED CONTROLS



6-SPEED DC COOLTOUCH™ CONTROL SYSTEM

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full Range Dimming
- No More Than Two Fans on One Circuit

OPTIONAL CONTROLS



6-SPEED DC WALL TRANSMITTER


370036 (Shown)

BLADE SPECS

Blade Finish & Part Number (Side 1)	Fan Finish (Reversible)
Silver FB300168 NI	NI Brushed Nickel
Walnut FB300168 PN	PN Polished Nickel

HANGING MEASUREMENTS

FLUSH MOUNT			
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 24.25"	B: 24.25"	C: 7.90"	D: 8.00"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5780	31	184

