

INCLUDED FEATURES

Blades (5) Included

- 12° Pitch
- 60" Sweep
- Reversible
- ABS

Downrods 12" Downrod with 1" (O.D.)

Downlight Replaceable. Integrated (1) 23W, 1600 Lumens LED Platform, 80 CRI, 3000K

Downlight Glass Fresnel Lens

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Flush Mount Canopy included. *Note: Décor trim must be removed for Flush Mount.*

Control CoolTouch™ Control System – Full Function

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 32.5 lbs.

Body Material Steel

Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 188mm X 25mm, AC

Amps 0.6 on High

RPM 157 on High

Energy Star® No

INCLUDED CONTROLS



COOLTOUCH™ CONTROL SYSTEM – FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Lights On/Off with Full-Range Dimming

OPTIONAL CONTROLS



WALL TRANSMITTER - FULL FUNCTION 370038MULTR (Shown)

COORDINATING LIGHTING

To see the complete Hatteras Bay™ Collection visit Kichler.com.

Outdoor Wall
49064OZ



Outdoor Wall
49067OZ



BLADE SPECS

Blade Finish & Part Number (Side 1)

Fan Finish (Reversible)



Distressed Antique Gray
FB310017 AVI



Walnut
FB310017 AVI



AVI
Anvil Iron



Cherry
FB310017 DBK



Walnut
FB310017 DBK



DBK
Distressed Black



Medium Walnut
FB310017 WZC



Dark Walnut
FB310017 WZC



WZC
Weathered Zinc


HANGING MEASUREMENTS

WITH 6" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 17.50"	B: 13.00"	C: 15.50"	D: 6.75"

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 12.25"	B: 7.75"	C: 15.50"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
6282	71	88

AIR PERFORMANCE (FLUSH)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5449	71	77