

INCLUDED FEATURES

Blades (5) Included

- 14° Pitch
- 52" Sweep
- Reversible
- ABS

Downrods 12" Downrod with 1" (O.D.)

Downlight Replaceable. Integrated (1) 23W Dimmable, 1600 Lumens LED Platform, 80 CRI, 3000K

Downlight Glass Fresnel Lens Gloss White Inside-Clear Outside

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Dual Mount Included. *Note: Décor trim must be removed for Flush Mount.*

Control CoolTouch™ Transmitter – Full Function

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 33 lbs.

Body Material Steel, Plywood, Glass

Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 172mm X 20mm, AC

Amps 0.69 on High

RPM 146 on High

Energy Star® No

INCLUDED CONTROLS



COOLTOUCH™ TRANSMITTER - FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Lights On/Off with Full-Range Dimming

OPTIONAL CONTROLS



WALL TRANSMITTER - FULL FUNCTION

370038MULTR (Shown)

BLADE SPECS

Blade Finish & Part Number (Side 1)	Blade Finish & Part Number (Reversible)	Fan Finish
Distressed Antique Gray FB310018 AVI	Walnut FB310018 AVI	AVI Anvil Iron
Cherry FB310018 DBK	Walnut FB310018 DBK	DBK Distressed Black
Medium Walnut FB310018 WZC	Dark Walnut FB310018 WZC	WZC Weathered Zinc


HANGING MEASUREMENTS

WITH 12" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 22.50"	B: 18.50"	C: 15.25"	D: 6.75"

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 11.25"	B: 7.25"	C: 15.25"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
6124	82	75

AIR PERFORMANCE (FLUSH)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4302	54	87