

INCLUDED FEATURES

Blades (3) Included

- 14° Pitch
- 54" Sweep
- Non-reversible
- ABS

Downrods Optional 337033 Downrod Kit

Downlight Replaceable. Includes (1) 17W Dimmable, 1600 Lumens LED Platform, 80 CRI, 3000K

Downlight Glass Etched Cased Opal Glass

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Flush Mount

Control Wall Transmitter – Full Function

FAN FEATURES

Mounting Slope – Pitch Flat ceiling only

Lead Wire 78"

cETL Listed Wet

Hanging Weight 18.2 lbs.

Body Material Steel

Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 172mm X 20mm, AC

Amps 0.59 on High

RPM 125 on High

Energy Star® No

INCLUDED CONTROLS



WALL TRANSMITTER – FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Lights On/Off with Full-Range Dimming


OPTIONAL CONTROLS



COOLTOUCH™ TRANSMITTER – FULL FUNCTION
337009 (Shown)

METAL CAPS

Includes a metal fixture cap for non-light use.



OPTIONAL HANGER SYSTEM



Downrod Kit
337033 MWH, NI, OZ (shown), SBK

BLADE SPECS


Blade Finish & Part Number (Side 1) **Fan Finish (Reversible)**

Matte White FB330152 MWH	MWH Matte White
Silver FB330152 NI	NI Brushed Nickel
Satin Black FB330152 SBK	SBK Satin Black
Brown FB330152 OZ	OZ Olde Bronze®

HANGING MEASUREMENTS

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 11.00"	B: 7.25"	C: 8.75"	D: 6.50"



OPTIONAL HANGER SYSTEM

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 15.00"	B: 11.25"	C: 8.75"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5096	70	73

AIR PERFORMANCE (OPT.)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5754	70	91